



SPECIFICATIONS

Part Number		YU4050K
Operating Pressure		4050 PSI
Max Pressure		4500 PSI
Max Flow		10.5 GPM
Max Temp		195° F
Banjo Size	Inlet:	1/2" BSP-F
	Outlet:	3/8" BSP-F
Port Size	Inlet:	1/2" BSP-F
	Outlet:	3/8" BSP-F
Dimensions		8" x 4.6" x 1.7"
Weight		0.86 lbs
Material		Brass, Stainless Steel, Plastic, Buna-N

General Pump recommends using a safety relief device in conjunction with this unloader valve when installed on a positive displacement pump. General Pump is not liable and assumes no responsibility when used in a customer's high pressure system.

PARTS LIST AND DIMENSIONS

No.	Part No.	Description	Qty.
1	Y60181131	Fitting, 3/8" BSP-F	1
2	Y10306601	O-Ring, 1.78 x 15.6 mm	2
3	Y60005351	Spring	1
4	Y60005251	Check Valve, SS	1
5	Y10321308	O-Ring, 3 x 6 mm	1
6	Y60172535	Valve Body	1
7	Y60180951	Seat	1
8	Y60180851	Shutter, M8	1
9	Y10306801	O-Ring, 1.78 x 17.17 mm	1
10	Y60181031	Spacer	1
11	Y60097924	Valve Piston Seal Kit	1
12	Y10307201	O-Ring, 1.78 x 20.35 mm	1
13	Y60097331	Piston Housing	1
14	Y16210000	Dowel, M4 x 4 mm	1
15	Y60172831	Lock Ring	1
16	Y60097824	Valve Piston Seal Kit	1
17	Y60180651	Piston, M8	1
18	Y14744310	Ball, 11/32", SS	1
19	Y60181331	Spring Guide	1
20	Y60097561	Spring, 4.5 x 47 mm	1
21	Y60172731	Cap, Brass	1
22	Y60172684	Cap	1
*	Y60161524	Repair Kit	

