

**SPECIFICATIONS**

Part Number:	#4.5	100487
	#5.5	100467
Rated Operating Pressure	4,200 PSI	
Maximum Operating Pressure	5,000 PSI	
Rated Temp	190° F (88° C)	
Inlet Port	1/4" NPT-F	
Dimensions	1-3/16" Hex x 3.5" Long	
Weight	.75 lbs	
Material	Brass, Stainless Steel, Buna-N, Plastic, Ceramic	

FEATURES

- Half the weight of competing nozzles - Lessens user fatigue
- Ideal for blasting applications

FLOW CHART

		Pressure (PSI)						
		2,000	2,500	3,000	3,500	4,000	4,200	5,000
GPM	100487 (#4.5)	3.18	3.56	3.90	4.21	4.50	4.61	5.03
	100467 (#5.5)	3.89	4.35	4.76	5.14	5.50	5.64	6.15

PARTS LIST

Item	Part #	Description	Qty.
1	510192	Viper Body, 1-3/16" Hex	1
2	660028*	Backup Ring, 018 Teflon, Split	1
3	700023*	O-ring, 90 Duro, Buna-N, .739" ID x .070" CS	1
4	510101	Endcap, 1-1/8" Hex	1
5	103027*	Seat Assembly	1
6	640053*	Rotor Tip	1
7	520094*	Viper Nozzle #4.5	1
	520095*	Viper Nozzle #5.5	1
8	10056402*	Rotor Assembly	1
9	660057	Viper Cover	1
*	100338	Repair Kit, #4.5	
*	100471	Repair Kit, #5.5	

Note: Torque item #4 (end cap) to 15 ft.-lbs

