

REAR ENTRY SPRAY GUNS - WEEP



REAR ENTRY SPRAY GUNS - WEEP						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG5000W	Standard	10.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG4010SW	Swivel	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG4000WN	Standard	10.5 GPM	4,050 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YRL2640W	Standard	8.0 GPM	4,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DG4000W	Standard	8.0 GPM	4,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DG5010W	Standard	10.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DGE4012W	Standard	12.0 GPM	4,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F

REAR ENTRY SPRAY GUNS STAINLESS STEEL



REAR ENTRY SPRAY GUNS - STAINLESS STEEL						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG1732	Cartridge	32.0 GPM	1,950 PSI	1/2" BSP-F	1/2" BSP-F	210° F
YG2953B	Cartridge	53.0 GPM	3,200 PSI	3/4" BSP-F	1/2" BSP-F	210° F
YG4060SS	Blue	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG5200	Red	10.5 GPM	6,400 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG7207	Compensating	7.5 GPM	8,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F

SPRAY GUN LANCE COMBINATIONS



SPRAY GUN / LANCE COMBINATIONS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
2100457	Locking, Dual Tr., 48" Lance	10.2 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	250° F
2100457L69	Locking, Dual Tr., 69" Lance	10.2 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	250° F
YG3000DS	16" Lance	10.5 GPM	3,050 GPM	3/8" NPT-F	1/8" NPT-F	140° F
YG3000D	40" Lance	10.5 GPM	3,050 GPM	3/8" NPT-F	1/8" NPT-F	140° F
YG34LA27	Gun, 27" Adjustable Lance, 3.5 mm Nozzle, 21.0 GPM					
YG29LA31	Gun, 31.5" Adjustable Lance, 2.3 mm Nozzle, 8.0 GPM					
YG5200/L42	YG5200 with Stainless Steel Lance					
YRL56L	42" Lance	8.0 GPM	5,650 PSI	3/8" NPT-F	1/4" NPT-F	320° F
Y30256717	YG5000 Assembled with 36" Lance and 1/4" Quick Disconnect					
100751	YG5000 Assembled with 18" Lance and 1/4" Quick Disconnect					
100059	YG4010 Assembled with 36" Lance and 1/4" Quick Disconnect					
101002	YG7207 Spray Gun with 36" Stainless Steel Lance, 7.5 GPM, 7,250 PSI					
100160	DG5010 Assembled with 36" Insulated/Vented Lance and 1/4" Quick Disconnect					
101057	DG5010 Assembled with 36" Insulated Lance and 1/4" Quick Disconnect					
101096	DG5010 Assembled with 48" Insulated Lance and 1/4" Quick Disconnect					
101109	DGE5010 Assembled with 24" Insulated Lance and 1/4" Quick Disconnect					
101110	DGE5010 Assembled with 36" Insulated Lance and 1/4" Quick Disconnect					
2100260	DG4000 Assembled with 36" Insulated Lance and 1/4" Quick Disconnect and 3/8" Plug Inlet, 8 GPM, 4000 PSI					



GP Companies, Inc
 1174 Northland Drive, Mendota Heights, MN 55120
 Phone: 651.686.2199 Fax: 800.535.1745
www.generalpump.com email: sales@gpcompanies.com
[facebook.com/gpcompanies](https://www.facebook.com/gpcompanies)



General Pump is part of the Interpump Group, the world leader in plunger pumps.



SPRAY GUNS & LANCE COMBINATIONS



REAR ENTRY SPRAY GUNS



REAR ENTRY SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
DCG5010	Compensating	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DCG5010HE	Hydro Excacating	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DG4000	Standard	8.0 GPM	4,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DG5010	Standard	10.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DGE5010	Standard	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DGE5010SL	Locking Trigger	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DGE4012NT	No Trigger	12.0 GPM	4,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
DG4512	Standard	12.0 GPM	4,500 PSI	3/8" NPT-F	1/4" NPT-F	320° F

REAR ENTRY SPRAY GUNS



REAR ENTRY SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG5000	Standard	10.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG4000	Standard	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG4010	Standard	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YRL56	Compensating	8.0 GPM	5,650 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YRL51	Compensating	13.2 GPM	4,050 PSI	3/8" NPT-F	1/4" NPT-F	320° F

STRAIGHT REAR ENTRY SPRAY GUNS



STRAIGHT REAR ENTRY SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
DG5000S	Straight	8.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	300° F
YG4500SW	Straight/Weep	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	300° F
YG4500S	Straight	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	300° F
YG4500ST	Straight, SS Inlet	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	300° F
YG2527S	Straight	27.0 GPM	2,500 PSI	1/2" NPT-F	1/2" NPT-F	320° F
YG4032S	Straight	32.0 GPM	4,050 PSI	1/2" NPT-F	1/2" NPT-F	320° F

FRONT ENTRY SPRAY GUNS



FRONT ENTRY SPRAY GUNS					
Model	GPM	MAX	INLET	OUTLET	MAX TEMP
DG2200	6.5 GPM	1,800 PSI	3/8" NTP-F	1/4" NTP-F	185° F
YRL20	8.0 GPM	3,200 PSI	3/8" BSP-F	1/4" BSP-F	320° F
ZGP11	10.5 GPM	3,000 PSI	3/8" BSP-F	1/4" BSP-F	285° F

HIGH FLOW REAR ENTRY WASH DOWN SPRAY GUNS



HIGH FLOW REAR ENTRY WASH DOWN SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG1635	Wash Down	16.0 GPM	350 PSI	1/2" BSP-F	Adj. Cone Nozzle	195° F
YG1635N	Wash Down	16.0 GPM	350 PSI	1/2" NPT-F	Adj. Cone Nozzle	195° F
YG1635S	Wash Down W/Swivel	16.0 GPM	350 PSI	1/2" BSP-F	Adj. Cone Nozzle	195° F
YG1635SR	Wash Down W/Swivel, SS Pin	16.0 GPM	350 PSI	1/2" BSP-F	Adj. Cone Nozzle	195° F
YG1635SS	Wash Down W/Swivel, 316 SS	16.0 GPM	350 PSI	1/2" BSP-F	Adj. Cone Nozzle	195° F
YG2635AS	Wash Down W/Swivel	26.5 GPM	350 PSI	1/2" BSP-F	Adj. Cone Nozzle	195° F

REAR ENTRY SPRAY GUNS - WITH CERAMIC BALL

REAR ENTRY SPRAY GUNS - CERAMIC BALL						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG5000C	Ceramic Ball	10.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG5000CS	Ceramic Ball and SS I/O	10.0 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	320° F
YG4500STC	Ceramic Ball / Straight	10.5 GPM	5,000 PSI	3/8" NPT-F	1/4" NPT-F	300° F