

**GENERAL PUMP** *A member of the Interpump Group*

- Eases system start-up. Especially useful for engine-driven pressure washers
- Fits any brand of pump
- Max working pressure of 5,000 PSI
- Designed and made in the USA
- Long-life construction
- Improved seal design limits leaks.

**SPECIFICATIONS**

See application chart on Page 2

|                                     |            |                                       |
|-------------------------------------|------------|---------------------------------------|
| Part Number: w/ Hosebarb:           | 1/4" NPT-M | 100324                                |
|                                     | 3/8" NPT-M | 100323                                |
| w/ NPT-F Port:                      | 1/4" NPT-M | 100543                                |
|                                     | 3/8" NPT-M | 100544                                |
|                                     | 1/2" NPT-M | 100490                                |
| Max Volume:                         |            | 8.0 GPM                               |
| Max Pressure                        |            | 5,000 PSI                             |
| Available Inlet Sizes               |            | 1/4", 3/8" or 1/2"                    |
| Hose Barb: (100324, 100325)         |            | 1/8"                                  |
| Port Size: (100543, 100544, 100490) |            | 1/8" NPT-F                            |
| Dimensions:                         |            | 2.1" L x 0.75" W                      |
| Weight:                             |            | .25 lb                                |
| Materials:                          |            | Brass, Stainless Steel, Thermoplastic |

**Bleeder Valve**

- Dramatically improves pump priming in suction conditions
- Max working pressure of 5,000 PSI
- Install on high pressure side of any pump
- Designed and made in the USA

**Must be plumbed before unloader****SPECIFICATIONS**

See application chart on Page 2

|  |            |                                       |
|--|------------|---------------------------------------|
| Part Number: w/ Hosebarb:                            | 1/4" NPT-M | 100325                                |
|  | 3/8" NPT-M | 100326                                |
| w/1/8" NPT-F Port:                                   | 1/4" NPT-M | 100545                                |
|  | 3/8" NPT-M | 100546                                |
| <i>Stiffer spring for electric start gas engines</i> |            |                                       |
| w/ Hose Barb   | 1/4" NPT-M | 100676                                |
|  | 3/8" NPT-M | 100684                                |
| Max Volume:  |            | 8.0 GPM                               |
| Max Pressure   |            | 5,000 PSI                             |
| Available Inlet Sizes                                |            | 1/4" or 3/8"                          |
| Hose Barb: (100324, 100325)                          |            | 1/8"                                  |
| Port Size: (100543, 100544, 100490)                  |            | 1/8" NPT-F                            |
| Dimensions:  |            | 2.1" L x 0.75" W                      |
| Weight:  |            | .25 lb                                |
| Materials:   |            | Brass, Stainless Steel, Thermoplastic |

***Choose appropriate valve  
from application chart below***

|  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Manual Start</li><li>• City Water</li></ul> <p><b>EZ Start</b></p>         | <ul style="list-style-type: none"><li>• Electric Starter</li><li>• City Water</li></ul> <p><b>Electric Start Bleeder</b></p> |
| <ul style="list-style-type: none"><li>• Manual Start</li><li>• Float Tank</li></ul> <p><b>Standard Bleeder</b></p> | <ul style="list-style-type: none"><li>• Electric Start</li><li>• Float Tank</li></ul> <p><b>Electric Start Bleeder</b></p>   |