

GENERAL PUMP *A member of the Interpump Group*

Foot Valves

A check valve with a strainer, typically installed on the inlet of the pump to maintain the prime of a pump.



2100016



2100017



2100018

FEATURES

- Stops particles from entering feed line
- Built in check valve to maintain pump prime
- Sturdy Stainless Steel and brass construction
- Easy to clean mesh screens
- Commonly used in reservoirs & tanks

SPECIFICATIONS

Part Number	2100016	2100017	2100018
Max Pressure	72 PSI		
Max Temperature	176° F		
Stainless Steel Screen	20 Mesh		
Port Size: Outlet	1/2-14 NPT-F	3/4-14 NPT-F	1-11.5 NPT-F
Dimensions	Ø1.3 x 2.8"	Ø1.3 x 3.1"	Ø1.3 x 3.5"
Weight	3.04 oz.	4.64 oz.	5.6 oz.
Material	Brass, Stainless Steel, ABS, Buna		

WARNINGS

WARNING: High Pressure Systems require a primary pressure regulating device (i.e. regulator, unloader) and a secondary pressure relief device (i.e. pop-off valve, relief valve). Failure to install such relief devices properly could result in personal injury or damage to pump or property. GP does not assume any liability or responsibility for the operation of the user's high pressure system.



WARNING: This product can expose you to chemicals including lead, which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



General Pump
is a member of
the Interpump Group



GENERAL PUMP 1174 Northland Drive • Mendota Heights, MN 55120
Phone: 651.686.2199 • Fax: 800.535.1745 • e-mail: sales@gpcompanies.com • www.generalpump.com

Ref 301145 Rev. A
11-23

